

Reference: UL-PL26PNTFCT-2G  
EAN13: 8057730787819

**Product title:**

Double Ferrule Thermoplastic light bulb socket - E26

**Product attributes:**

Finish: White, Black

**Product image:**



**Product price:**

\$3.90 tax included

**Product short description:**

These double ferrule thermoplastic light sockets work with almost all of our pendant light lampshades, including all of our super popular fiber string lampshades and handmade Italian ceramic pendant light shades.

So, why do we call them double ferrule? It's a fancy way of saying two rings. And that's exactly what these light bulb sockets have on them, two rings. The rings are there to hold pendant light shades in place. Most pendant light shade that have an opening between 1 - 5/8 inches to 2 - 1/16 inches wide should work with these double ferrule light bulb sockets.

This double ferrule thermoplastic E26 socket is made in Italy to the highest standards. It's UL listed and works with standard/medium E26 base light bulbs. A fantastic socket at a great price. This socket works with all our pendant light cables.

**WARNING: a strain relief cable clamp is NOT included.** On our website go to Lamp Parts & Shades > Lighting Accessories > Strain Reliefs to select the strain relief to go with your light bulb socket. Any of our strain reliefs will work with this light bulb socket.

UL Listed: E190302

**Product description:**

Cover: threaded.

Rated voltage: 250 Vac.

Terminals: screw terminals for rigid or flexible cables from 0.50 to 2.50 mm<sup>2</sup>.

Fixing: with threaded hole M10x1.

**Dimensions**

Diameter : 1 - 3/4 inches (40 mm)

Height: 2 - 1/8 inches (54 mm)

Diameter of ring nut : 2 - 3/16 inches (56 mm)

UL Listed: E190302

Note that this double ferrule thermoplastic light bulb socket has a built-in locking safety device that does not allow you to unscrew it once assembled. (This is to protect you from electric shock.)

We ship all our light sockets

not fully assembled and twisted closed

so that the built-in locking safety mechanism is not "locked" when you receive it. If the safety device does somehow become locked you can unlock this security system, located inside the socket on the side, with a small screwdriver. Please see our tutorial page for videos on how to unlock these light bulb sockets. And If you attempt to unlock the socket you must have the power

Disconnected

to the socket before inserting anything into the socket!

**Product features:**

Material: Phenolic

Ferrule: Yes

Fitting: E26

**Product gallery:**

